

GFQ-D-2458 Cavity Power Splitter Series

Technical Sheet

Main Features

- 2400-6000MHz broadband
- 2400-6000MHz communication system
- Low insertion loss, Low VSWR, Low passband ripple
- Coaxial cavity structure



Electrical Specifications

Model	GFQ-2D-2458	GFQ-3D-2458	GFQ-4D-2458
Frequency Range-MHz	2400~6000		
VSWR	≤ 1.3		
Insertion Loss-dB	≤ 3.3	≤ 5.1	≤ 6.2
Nominal Impedance- Ω	50		
Power Capacity-W	200		

Mechanical & Environmental Specifications

Connector	N-K		
Dimensions(L×W×H)-mm	118×64×26	139×64×26	127×64×45
Weight-g	250	280	280
Operating Temperature- $^{\circ}\text{C}$	-40 $^{\circ}\text{C}$ ~+60		
Relative Humidity	5~95%		

Optional

Various adapters, cables and jumper cables etc.



Kenbotong Technology Co., Ltd.

Addr :NO.2 Chanxiu Road ,Foshan city,Guangdong China Code:528061
Tel: 86(757)8202-5597, 8221-9788 Fax : 86(757)8221-2072,8802-2808
Email: kbt@kenbotong.com web: <http://www.kenbotong.com>