



PELTOR™ **E•A•R.**





3M™ Peltor™ ComTac™ XS

Electronic Level Dependent Hearing Protector



MT15H69FB-02 378

- Slim cup design
- Level dependent function in stereo
- Last setting is stored when switched off
- Fully independent dual earphone system for active volume and external radio signal, for maximum security
- Automatically switches off after two hours if no function is used. Two signals are emitted as a warning that the ComTac will switch off in one minute if no function is activated
- Battery life is about 250 hours. Three warning signals are emitted every 30 seconds for five minutes when power is low, then the headset switches off
- Audio input jack to allow connection to an external radio
- Available as headset

Description	3M product code	Peltor product code	Attachment	Weight (g)	Colour
Standard	XH001660238	MT15H69FB-02 378	Foldable head band	295	 
Standard	XH001660253	MT15H69FB-08 378SV	Foldable head band	295	 

MT15H69FB-** ***

Frequency (Hz)	125	250	500	1000	2000	4000	8000
Mean Attenuation (dB)	14.4	17.4	24.1	31.1	31.5	38.1	37.3
Standard Deviation (dB)	4.8	3.4	3	2.2	3	2.8	3.2
Assumed Protection (dB)	9.6	14	21.1	28.9	28.5	35.3	34.1

SNR=26dB H=31dB M=24dB L=16dB